










Typical Apperance	Model	Series	Pin Dia.(mm)	Base Dia. (mm)	Length (mm)	Thread
	L1-10.7-60-M26	Pneumatic Aluminum Shell	1	10.7	60	M26
	LS2-7.5-100-M24	Pneumatic Aluminum Shell	2	7.5	100	M24
	LS2-8-60-M26	Pneumatic Customized	2	8	60	M26
	L2.5-6-56-M26	Pneumatic Aluminum Shell	2.5	6	56	M26
	G3-10-75-M27	Pneumatic Steel Shell	3	10	75	M27
	L3-10.7-85-M26	Pneumatic Aluminum Shell	3	10.7	85	M26
	T3-12-62-M26	Pneumatic Steel Shell	3	12	62	M26
	LS3-12-63-M24	Pneumatic Customized	3	12	63	M24
	LS3-14-65-M24	Pneumatic Customized	3	14	65	M24
	T3-12-93-M26	Pneumatic Customized	3	12	93	M26
	L3-12.8-58-M26	Pneumatic Aluminum Shell	3	12.8	58	M26
	T3-16.5-60-M26	Pneumatic Copper Shell	3	16.5	60	M26
	T4-16.5-60-M26	Pneumatic Copper Shell	4	16.5	60	M26
	L4-17.2-65-M26	Pneumatic Aluminum Shell	4	17.2	65	M26
	L4-17.2-120-M26	Pneumatic Aluminum Shell	4	17.2	120	M26
	LS4-20-65-M30	Pneumatic Customized	4	20	65	M30
	T5-17-96-M26	Pneumatic Copper Shell	5	17	96	M26
	T5-20-67-M32	Pneumatic Copper Shell	5	20	67	M32

	T6-20-108-M26	Pneumatic Copper Shell	6	20	108	M26
	LS6-25-95-M34	Pneumatic Customized	6	25	95	M34
	LS6-33-97-M45	Pneumatic Aluminum Shell	6	33	97	M45
	LS12-33-97-M45	Pneumatic Aluminum Shell	12	33	97	M45
	E4-39-84	Electric Dotting	4	39	84	Electric Base
	E4-39-110	Electric Dotting	4	39	110	Electric Base
	G6-27-58	Pneumatic Scribing	6	27	58	Scriber Base
	G8-27-59	Pneumatic Scribing	8	27	59	Scriber Base
	G8-49-64	Pneumatic Scribing	8	49	64	Scriber Base